



INSTALLATION INSTRUCTIONS

Accessory
FULL NOSE MASK
P/N 08P35-TE0-100A


Application
2012 ACCORD
2-DOOR

Publications No.
All 46518
Issue Date
AUG 2011


Put this information in the glove box with the vehicle owner's manual.

PARTS LIST

Mask
(hood section)



Mask
(hood section)



2 Snap-screws A



2 Snap-screws B




2 Washers




2 Fenderwell nuts



Elastic cord



Storage bag




TOOLS AND SUPPLIES REQUIRED

Stubby Phillips screwdriver

Flat-tip screwdriver

Scissors

Illustration of the Full Nose Mask installed on the vehicle



INSTALLATION

Customer Information: The information in this installation instruction is intended for use only by skilled technicians who have the proper tools, equipment, and training to correctly and safely add equipment to your vehicle. These procedures should not be attempted by “do-it-yourselfers.”


NOTE:

- Make sure the vehicle and nose mask are clean and completely dry before installation. If moisture under the mask is allowed to dry, it may cloud the paint. If the mask gets wet, remove and allow it to air-dry completely.
- Make sure any repainted surfaces are cured.
- Make sure the hood and nose of the vehicle have been waxed with a high-quality paste wax.
- Make sure to install the nose mask securely. If the nose mask starts to flap or comes loose while driving, safely pull to the side of the road, stop the vehicle, and secure or remove the nose mask.
- The nose mask cannot be installed if the vehicle is equipped with front under spoilers.

Displaying the License Plate


If your state law requires the display of both license plates, cut out the piece of the bumper section that covers the front license plate:

- Face the inside of the mask toward you.
- Carefully cut out the overcast stitching with scissors. Remove the stitching and license plate section.




Installing the Hood Section

1. Open the hood. Fit the corners of the hood section around the hood. Adjust the mask so that it fits smoothly over the edges. Attach two hooks to the 15 mm hole (large hole) in the hood. When removing or installing the hooks, insert your finger or thumb into the loop of each hook as shown. Pulling the hooks with excessive force can break the hook strap.




Installing the Bumper Section

2. Turn the steering wheel fully clockwise.
3. Remove the expansion clip that fastens the inner fender, then clean the area around the hole.




4. Pull the inner fender down, and insert one fenderwell nut into the hole in the left front fender.
5. Place a washer onto the snap-screw A, then install and securely tighten snap-screw A into the fenderwell nut.
6. Remove one self-tapping screw from the left front fender. Install and securely tighten snap-screw B in its place.
7. Turn the steering wheel fully counterclockwise, and repeat steps 3 through 6 on the right side.


8. Pull the mask back toward the fenderwell, smooth out any wrinkles, and then snap the mask onto the snap-screws A and B.




9. Attach two plastic hooks to the fenderwell.
10. Repeat steps 8 and 9 on the right side.
11. Insert nine tabs between the left headlight and the bumper/fender. Repeat on the right side.




12. Attach one hook to the left side engine cover. Repeat on the right side.




13. Attach two hooks to the edge of the radiator cover.




14. Attach four plastic hooks to the inside edge of the front bumper.




15. Attach six hooks to the inside edge of the front bumper.




16. Attach two hooks to the inside edge of the front bumper.



17. Attach four plastic hooks to the inside edge of the front bumper.



18. Route the elastic cord through the twelve loops on the bottom of the mask. Attach one hook to the hole in the inner fender. Stretch the elastic cord and attach the other hook to the inner fender hole on the other side.



CLEANING THE NOSE MASK

Use a sponge or cloth and a solution of mild liquid dishwashing soap and water to clean the vinyl and the flannel backing. Rinse the mask completely with clean water, and hang it to dry out of direct sunlight. Make sure the mask is completely dry before you reinstall it.